



Videssence™

KOLDKITS

SYSTEM

Koldlite Lighting Kits allow safe, compact storage or transportation of your fixtures for location, ENG or OB lighting environments. The versatile fixtures and accessories provide the location lighting director with volumes of light while using minimal electricity. Each kit is complete with necessary accessories including folding stands, power cords, barn doors and two sets of lamps. All 230 volt fixtures are RoHS compliant.



Double Fixture KOLDKITS

KK2110-SC(*) KOLDKIT

Kit Includes:

- (2) K110(*) Volt Non-Dim Fixture
110 watt compact fluorescent multi-purpose fixture that provides even coverage for short throw studio, ENG or OB lighting applications.
- (2) BD-K110 four leaf Barn Door
- (2) MT-LOS-KH folding Heavy Kit Stand
- (2) MT-MH-BS 5/8" Baby Spud mounting adapter
- (2) CB-P-16 16' Standard Power Cord
- (4) LBX55/32 Tungsten Color 55 watt Biax Lamp
- (4) L-BX55/55 Daylight Color 55 watt Biax Lamp
- (1) CS-KK2110-SC Standard Case

Overall size: 32.25"L x 13.75"W x 18.25"Ht.

KK2220-SC(*) KOLDKIT

Kit Includes:

- (2) K220(*) Volt Non-Dim Fixture
220 watt compact fluorescent multi-purpose fixture that provides even coverage for medium throw studio, ENG or OB lighting applications. Two integral switches at the back of the fixture allow separate switching of each pair of lamps.
- (2) BD-K110 four leaf Barn Door
- (2) MT-LOS-KH folding Heavy Kit Stand
- (2) MT-MH-BS 5/8" Baby Spud mounting adapter
- (2) CB-P-16 16' Standard Power Cord
- (8) L-BX55/32 Tungsten Color 55 watt Biax Lamp
- (8) L-BX55/55 Daylight Color 55 watt Biax Lamp
- (1) CS-KK2220-SC Standard Case

Overall size: 32.5"L x 16"W x 22.5"Ht.

* add 1= 120/volt OR add 2= 230/volt

KK2110-FC(*) KOLDKIT

Kit Includes:

- (2) K110(*) Volt Non-Dim Fixture
110 watt compact fluorescent multi-purpose fixture that provides even coverage for short throw studio, ENG or OB lighting applications.
- (2) BD-K110 four leaf Barn Door
- (2) MT-LOS-KH folding Heavy Kit Stand
- (2) MT-MH-BS 5/8" Baby Spud mounting adapter
- (2) CB-P-16 16' Standard Power Cord
- (4) LBX55/32 Tungsten Color 55 watt Biax Lamp
- (4) L-BX55/55 Daylight Color 55 watt Biax Lamp
- (1) CS-KK2110-FC Flight Case.

Overall size: 32.25"L x 13.75"W x 20"Ht.

KK2220-FC(*) KOLDKIT

Kit Includes:

- (2) K220(*) Volt Non-Dim Fixture
220 watt compact fluorescent multi-purpose fixture that provides even coverage for medium throw studio, ENG or OB lighting applications. Two integral switches at the back of the fixture allow separate switching of each pair of lamps.
- (2) BD-K110 four leaf Barn Door
- (2) MT-LOS-KH folding Heavy Kit Stand
- (2) MT-MH-BS 5/8" Baby Spud mounting adapter
- (2) CB-P-16 16' Standard Power Cord
- (8) L-BX55/32 Tungsten Color 55 watt Biax Lamp
- (8) L-BX55/55 Daylight Color 55 watt Biax Lamp
- (1) CS-KK2220-FC Flight Case with integral wheels

Overall size: 32.5"L x 16"W x 24.5"Ht.

Measurements given are inches (B.S.U.) Ref: 1" = 2.54cm.

Single Fixture KOLDKITS KK1110-ENG(*) KOLDKIT

Our smallest available kit for lighting on the run. This single fixture Kit is very light weight and features a soft case with backpack straps for ease of handling and balancing the weight. All 230 volt fixtures are RoHS compliant.

FIXTURES K110



This is a versatile, short throw location lighting fixture. It is small and easy to handle or mount in tight quarters. The .063 formed aluminum housing has a textured black TGIC polyester powder coat finish. It utilizes two 55 watt Fluorescent Biax lamps. The fixture produces an equivalent

amount of visible light to a 1000 watt incandescent soft light, but only uses 110 watts of electricity. Size: 24.25" x 2.9" x 13.12"

	Distance				
	3ft./1.91m	6ft/1.83m	9ft/2.74m	12ft/3.66m	15ft/4.57m
FC	269	86	38	22	15
Lux	2897	926	409	237	162

CASES Standard Case



The standard field case is made of black thermal formed polyurethane material, with metal leading edges, metal corner framing and dense foam lining. It has a spring loaded carrying handle on the top of the case. This case provides protection for the fixtures,

lamps, and accessories when being stored in the field. Inside the case is compartmentalized so individual components of the kit are not damaged in transport. The layout of the case makes it possible to open it, reach the stands first, place the fixtures on the stands and go to work.

Kit Includes:

- (1) K110(*) Volt Non-Dim Fixture
110 watt compact fluorescent multi-purpose fixture that provides even coverage for short throw studio, ENG or OB lighting applications.
- (1) BD-K110 four leaf Barn Door
- (1) MT-LOS-KH folding Heavy Kit Stand
- (1) MT-MH-BS 5/8" Baby Spud mounting adapter
- (1) CB-P-16 16' Standard Power Cord
- (2) LBX55/32 Tungsten Color 55 watt Biax Lamp
- (2) L-BX55/55 Daylight Color 55 watt Biax Lamp
- (1) CS-KK1110-ENG Soft Case

Overall size: 32"L x 5"W x 25"Ht.

* add 1= 120/volt OR add 2= 230/volt

K220



This is a powerful, high output location lighting fixture. The .063 formed aluminum housing has a textured black TGIC polyester powder coat finish. It utilizes four 55 watt Fluorescent Biax lamps and each pair can be separately switched. In full "on" this fixture produces an equivalent

amount of visible light to a 2000 watt incandescent soft light, but only uses 220 watts of electricity. Size: 24.75" x 2.9" x 17.8"

	Distance				
	3ft./1.91m	6ft/1.83m	9ft/2.74m	12ft/3.66m	15ft/4.57m
FC	435	112	52	31	21
Lux	4683	1206	560	334	221

Flight Case



The heavy duty flight case is made of fiberglass laminate, internally framed with light metal and has metal corner braces, metal corner framing and dense foam lining. There are several recessed, spring loaded carrying handles for lifting and carrying the case. The larger

unit #CS-KK2220-FC has recessed casters for rolling. The case is configured so all equipment is accessible from the top. Inside the case is divided into foam lined compartments, which protect each component in transport. This case can be shipped on airlines or overland and should provide years of service.

Measurements given are inches (B.S.U.) Ref: 1"=2.54cm.